

		Frame Size	ST	HT	CS	TT	Reach	Stack	Stand	FC	WB	BB	HA	SA	Fork Axle
Melt EVO	-	U	335	115	381	585	397	574	0	0	1033	-25	69	72	495
Melt	-	U	335	115	381	585	397	574	0	0	1033	-25	69	72	495
(AM) Zircus frame	-	U	335	115	381	585	397	574	0	0	1033	-25	69	72	495
Melt Pump	-	U	335	115	381	585	397	574	0	0	1033	-25	69	72	495
Diezel Silver	-	U	306	115	381	605	397	555	0	0	1036	-4	69	70	495
OMG	S	S	410	110	442	596	430	618	0	0	1186	-40	65,5	75	550
OMG	M	M	440	120	442	624	455	631	0	0	1215	-40	65,5	75	550
OMG	L	L	475	130	442	651	480	637	0	0	1244	-40	65,5	75	550
OMG EVO	S	S	410	110	442	596	430	618	0	0	1186	-40	65,5	75	550
OMG EVO	M	M	440	120	442	624	455	631	0	0	1215	-40	65,5	75	550
OMG EVO	L	L	475	130	442	651	480	637	0	0	1244	-40	65,5	75	550
BRRAP	S	S	390	100	433	584	414	596	791	744	1177	-2	64,5	74,5	565
BRRAP	M	M	430	110	433	612	439	605	766	773	1206	-2	64,5	74,5	565
BRRAP	L	L	450	110	433	637	464	605	760	798	1231	-2	64,5	74,5	565
BRRAP	XL	G	490	120	433	666	489	614	766	827	1260	-2	64,5	74,5	565
Hooner	S/M	M	415	102	430	642	480	487	0	800	1223	-60	64	74	531
Hooner	L/XL	L	460	110	435	675	499	519	0	823	1246	-60	64	74	531
Prone 29"	S	S	432	104	425	589	415	627	0	0	1132	-60	66,5	74,5	531
Prone 29"	M	M	470	115	425	611	435	636	0	0	1156	-60	66,5	74,5	531
Prone 29"	L	L	520	125	425	638	460	645	0	0	1185	-60	66,5	74,5	531
Sour	S	S	407	105	420	587	415	618	0	0	1132	-55	65	74,5	560
Sour	M	M	445	115	420	610	436	628	0	0	1156	-55	65	74,5	560
Sour	L	L	495	125	420	637	460	637	0	0	1185	-55	65	74,5	560
GRD 1	S	S	475	125	428	545	379	526		609	1026	-70	69,5	73	400
GRD 1	M	M	510	145	428	560	387	569		615	1033	-71	70,5	73	400
GRD 1	L	L	540	170	428	581	400	592		636	1055	-71	70,6	73	400
GRD 1	XL	G	570	200	428	599	410	620		656	1075	-70	70,7	73	400
GRD 2	S	S	495	110	420	538	373	538	0	0	996	-70	71	73	400
GRD 2	M	M	530	130	420	553	382	559	0	0	1007	-70	71,5	73	400
GRD 2	L	L	560	160	420	570	391	587	0	0	1026	-70	71,5	73	400
GRD 2	XL	G	590	180	420	585	400	606	0	0	1041	-70	71,5	73	400

GRD 2	S	S	495	110	420	538	373	538	0	0	996	-70	71	73	400
GRD 2	M	M	530	130	420	553	382	559	0	0	1007	-70	71,5	73	400
GRD 2	L	L	560	160	420	570	391	587	0	0	1026	-70	71,5	73	400
GRD 2	XL	G	590	180	420	585	400	606	0	0	1041	-70	71,5	73	400
GRD Flat	S	S	495	110	420	538	373	538	0	0	996	-70	71	73	400
GRD Flat	M	M	530	130	420	553	382	559	0	0	1007	-70	71,5	73	400
GRD Flat	L	L	560	160	420	570	391	587	0	0	1026	-70	71,5	73	400
GRD Flat	XL	G	590	180	420	585	400	606	0	0	1041	-70	71,5	73	400
Kode	S	S	480	115	425	550	379	555	0	0	1009	-70	71,5	73	400
Kode	M	M	510	130	425	560	385	572	0	0	1014	-70	72	73	400
Kode	L	L	540	152	425	580	398	592	0	0	1009	-70	72	73	400
Kode ADV	S	S	480	135	425	555	380	571	0	0	1019	-70	71	73	400
Kode ADV	M	M	510	150	425	569	390	585	0	0	1034	-70	71	73	400
Kode ADV	L	L	540	172	425	585	400	606	0	0	1051	-70	71	73	400
Kode ADV	XL	G	407	185	430	596	407	619	0	0	1067	-70	71	73	400
Kode ADV	S	S	480	135	425	555	380	571	0	0	1019	-70	71	73	400
Kode ADV	M	M	510	150	425	569	390	585	0	0	1034	-70	71	73	400
Kode ADV	L	L	540	172	425	585	400	606	0	0	1051	-70	71	73	400
Kode ADV	XL	G	407	185	430	596	407	619	0	0	1067	-70	71	73	400
Flapjack	S	S	490	124	445	555	379	567	0	0	1076	-75	69	73	420
Flapjack	M	M	510	153	445	574	390	594	0	0	1097	-75	69	73	420
Flapjack	L	L	530	164	445	599	410	614	0	0	1103	-75	69	73	420
Flapjack	XL	G	550	182	445	614	420	631	0	0	1119	-75	69	73	420