

Sheet1

	Size	Reach	Stack	Front center	Effective TT	HT	ST	Chainstay	BB drop	HT angle	ST angle	ForkAxle to Crown	Fork Offset	Crank Length	Bar width	Stem	
		mm	mm	mm	mm	mm	mm	mm	mm	degre	degre	mm	mm	mm	mm	mm	
RUUT TI	LO	S	373	536	586	534	110	475	420	70	71	73	400	45	170	420	80
		M	383	557	596	551	130	510	420	70	71.5	73	400	45	172.5	440	90
		L	391	582	615	569	160	540	420	70	71.5	73	400	45	172.5	440	90
		XL	400	606	630	584	180	570	420	70	71.5	73.8	400	45	175	460	110
	HI	S	381	531	594	532	110	475	420	76	71.8	73.8	390	55	170	420	80
		M	391	552	605	553	130	510	420	74	72.3	73.8	390	55	172.5	440	90
		L	397	572	625	571	160	540	420	74	72.3	73.8	390	55	172.5	440	90
		XL	406	601	640	586	180	570	420	74	72.3	73.8	390	55	175	460	110
RUUT CF	LO	S	374	536	591	538	110	495	420	70	70.5	73	400	45	170	420	80
		M	382	558	597	553	130	530	420	70	71.5	73	400	45	172.5	440	90
		L	392	587	615	571	160	560	420	70	71.5	73	400	45	172.5	440	90
		XL	400	606	630	585	180	590	420	70	71.5	73	400	45	175	460	110
	HI	S	381	531	601	536	110	495	420	74	71.3	73.8	390	55	170	420	80
		M	390	553	606	551	130	530	420	74	72.3	73.8	390	55	172.5	440	90
		L	400	582	625	569	160	560	420	74	72.3	73.8	390	55	172.5	440	90
		XL	406	601	638	579	180	590	420	73.8	72.3	73.8	390	55	175	460	110
RUUT AL	LO	XS	371	519	588	530	100	450	420	65	70	73	400	45	165	420	80
		S	374	536	591	538	110	475	420	70	70.5	73	400	45	170	420	80
		M	382	558	597	553	130	510	420	70	71.5	73	400	45	172.5	440	90
		L	392	587	615	571	160	540	420	70	71.5	73	400	45	172.5	440	90
		XL	400	606	630	585	180	570	420	70	71.5	73	400	45	175	460	110
	HI	XS	378	516	596	528	100	450	420	70	70.7	73.7	290	55	165	420	80
		S	381	531	601	536	110	475	420	74	71.3	73.8	390	55	170	420	80
		M	390	553	606	551	130	510	420	74	72.3	73.8	390	55	172.5	440	90
		L	400	582	625	569	160	540	420	74	72.3	73.8	390	55	172.5	440	90
XL	406	601	638	579	180	570	420	73.8	72.3	73.8	390	55	175	460	110		
RUUT ST1	LO	S	373	536	586	534	110	475	420	70	70.5	73	400	45	170	420	80
		M	383	557	596	551	130	510	420	70	71.5	73	400	45	172.5	440	90
		L	391	582	615	569	160	540	420	70	71.5	73	400	45	172.5	440	90
		XL	400	606	630	584	180	570	420	70	71.5	73	400	45	175	460	110
	HI	S	381	531	594	532	110	475	420	74	71.3	73.8	390	55	170	420	80
		M	391	552	605	553	130	510	420	74	72.3	73.8	390	55	172.5	440	90

Sheet1

	Size	Reach	Stack	Front center	Effective TT	HT	ST	Chainstay	BB drop	HT angle	ST angle	ForkAxle to Crown	Fork Offset	Crank Length	Bar width	Stem		
RUUT ST2	HI	L	397	572	625	571	160	540	420	74	72.3	73.8	390	55	172.5	440	90	
		XL	406	601	640	586	180	570	420	73.8	72.3	73.8	390	55	175	460	110	
		S	373	536	586	534	110	495	420	70	70.5	73	400	45	170	420	80	
		LO	M	383	557	596	551	130	530	420	70	71.5	73	400	45	172.5	440	90
			L	391	582	615	569	160	560	420	70	71.5	73	400	45	172.5	440	90
			XL	400	606	630	584	180	590	420	70	71.5	73	400	45	175	460	110
			S	381	531	594	532	110	495	420	74	71.3	73.8	390	55	170	420	80
		HI	M	391	552	605	553	130	530	420	74	72.3	73.8	390	55	172.5	440	90
			L	397	572	625	571	160	560	420	74	72.3	73.8	390	55	172.5	440	90
			XL	406	601	640	586	180	590	420	73.8	72.3	73.8	390	55	175	460	110
	HVRT CF		S51	372	520	568	532	111	500	408	67	71.6	72.8	380	40	170	400	90
			LO	M54	378	553	581	551	144	530	408	67	72.1	72.6	380	40	172.5	420
			L56	388	570	589	566	160	550	408	67	72.8	72.6	380	40	172.5	420	110
			XL59	400	605	608	589	195	570	410	67	73.1	72.6	380	40	175	440	110
			S51	378	515	571	531	111	500	408	72	72.3	73.5	370	45	170	400	90
		HI	M54	385	548	584	550	144	530	408	72	72.8	73.3	370	45	172.5	420	90
MUTT AL		L56	394	566	592	564	160	550	408	72	73.5	73.3	370	45	172.5	420	110	
		XL59	407	600	614	587	195	570	410	72	73.8	73.3	370	45	175	440	110	
		S	368	534	565	530	125	490	415	67	72	73	380	40	170	400	90	
		LO	M	375	558	580	545	150	520	415	67	72	73	380	40	172.5	420	90
			L	380	588	590	560	180	540	415	67	72.5	73	380	40	172.5	420	110
			XL	391	608	607	577	195	570	415	67	72.5	73	380	40	175	440	110
			S	373	530	567	528	125	490	415	72	72.7	73.7	370	45	170	400	90
		HI	M	381	553	583	543	150	520	415	72	72.7	73.7	370	45	172.5	420	90
			L	387	584	593	558	180	540	415	72	73.2	73.7	370	45	172.5	420	110
MUTT ST		XL	398	603	610	575	195	570	415	72	73.2	73.7	370	45	175	440	110	
		S	367	530	565	530	120	490	415	67	72	73	380	40	170	400	90	
		LO	M	375	558	580	545	150	520	415	67	72	73	380	40	172.5	420	90
			L	380	588	590	560	180	540	415	67	72.5	73	380	40	172.5	420	110
			XL	391	608	607	577	195	570	415	67	72.5	73	380	40	175	440	110
		HI	S	375	525	567	528	120	490	415	72	72.7	73.7	370	45	170	400	90
		M	381	553	583	543	150	520	415	72	72.7	73.7	370	45	172.5	420	90	

Sheet1

	Size	Reach	Stack	Front center	Effective TT	HT	ST	Chainstay	BB drop	HT angle	ST angle	ForkAxle to Crown	Fork Offset	Crank Length	Bar width	Stem		
BOGAN ST	HI	L	387	584	593	558	180	540	415	72	73.2	73.7	370	45	172.5	420	110	
		XL	398	603	610	575	195	570	415	72	73.2	73.7	370	45	175	440	110	
		S	401	582	636	575	140	470	435	80	70	73	400	45	170	440	60	
		LO	M	406	601	647	585	160	490	435	80	70	73	400	45	172.5	440	60
			L	414	619	663	600	180	510	435	80	70	73	400	45	172.5	460	80
			XL	424	638	680	620	200	530	435	80	70	73	400	45	175	460	80
			S	409	577	644	573	140	470	435	86	70.8	73.8	390	55	170	440	60
		HI	M	413	595	655	583	160	490	435	86	70.8	73.8	390	55	172.5	440	60
			L	423	611	671	598	180	510	435	86	70.8	73.8	390	55	172.5	460	80
			XL	432	633	680	618	200	530	435	86	70.8	73.8	390	55	175	460	80
			S	395	555	609	560	130	495	420	70	71.5	73	400	45	170	660	80
	BOOZ ST		LO	M	406	585	630	580	530	420	70	71.5	73	400	45	170	680	90
			L	420	603	650	600	560	420	70	71.5	73	400	45	175	680	90	
			XL	434	622	670	620	590	420	70	71.5	73	400	45	175	700	100	
			S	403	550	616	558	495	420	76	72.3	73.8	390	55	170	660	80	
		HI	M	414	580	637	578	530	420	76	72.3	73.8	390	55	170	680	90	
			L	428	597	657	598	560	420	75	72.3	73.8	390	55	175	680	90	
		XL	442	616	677	617	590	420	75	72.3	73.8	390	55	175	700	100		
RATT CF		S	369	534	575	532	110	490	415	70	72,2	73	392	50	170	400	90	
		LO	M	380	557	593	550	520	415	70	72,2	73	392	50	172.5	420	90	
			L	388	581	608	565	540	415	70	72,2	73	392	50	172.5	420	110	
			XL	400	610	630	586	570	415	70	72,2	73	392	50	175	440	110	
			S	376	529	583	530	490	415	75	72,9	73,7	382	60	170	400	90	
		HI	M	387	552	601	548	520	415	75	72,9	73,7	382	60	172.5	420	90	
			L	395	576	617	564	540	415	75	72,9	73,7	382	60	172.5	420	110	
		XL	407	605	638	584	570	415	75	72,9	73,7	382	60	175	440	110		
MYLC CF		S	405	552	652	572	130	435	425,0	70,0	68,00	73,40	400	45,0	170	420	50,0	
		LO	M	418	575	674	589	467	425,0	70,0	68,00	73,40	400	45,0	172.5	440	50,0	
			L	430	602	697	609	485	425,0	70,0	68,00	73,40	400	45,0	172.5	460	70,0	
			XL	440	630	718	628	515	425,0	70,0	68,00	73,40	400	45,0	175	460	70,0	
			S	410	548	657	570	435	425,0	75	68.6	74	390	55	170	420	50,0	
		HI	M	423	571	679	587	467	425,0	75	68.6	74	390	55	172.5	440	50,0	

Sheet1

	Size	Reach	Stack	Front center	Effective TT	HT	ST	Chainstay	BB drop	HT angle	ST angle	ForkAxle to Crown	Fork Offset	Crank Length	Bar width	Stem		
MYLC AL	HI	L	435	598	702	607	184	485	425,0	75	68.6	74	390	55	172.5	460	70,0	
		XL	445	626	723	626	214	515	425,0	75	68.6	74	390	55	175	460	70,0	
	LO	XS	382	522	619	538	110	435	425,0	65,0	68,00	73,40	400,0	45,0	165	400,0	50,0	
		S	412	552	659	577	137	460	425,0	70,0	68,00	73,40	400,0	45,0	170	420	50,0	
		M	421	570	676	591	157	485	425,0	70,0	68,00	73,40	400,0	45,0	172.5	440	50,0	
		L	433	600	699	612	189	510	425,0	70,0	68,00	73,40	400,0	45,0	172.5	460	70,0	
		XL	442	629	720	630	220	530	425,0	70,0	68,00	73,40	400,0	45,0	175	460	70,0	
		XS	387	518	624	536	110	435	425,0	70	68.6	74	390	55	165	400,0	50,0	
		S	417	548	664	575	137	460	425,0	75	68.6	74	390	55	170	420	50,0	
		HI	M	426	566	681	589	157	485	425,0	75	68.6	74	390	55	172.5	440	50,0
			L	438	596	704	610	189	510	425,0	75	68.6	74	390	55	172.5	460	70,0
		XL	447	625	725	628	220	530	425,0	75	68.6	74	390	55	175	460	70,0	
	MYLC ST	XS	380,0	530,0	620,0	538,0	110	435	425,0	65,0	68,00	73,40	400,0	45,0	165	400,0	50,0	
		S	410,0	554,0	658,0	575,0	130	460	425,0	70,0	68,00	73,40	400,0	45,0	170	420	50,0	
		M	420,0	572,0	676,0	591,0	150	485	425,0	70,0	68,00	73,40	400,0	45,0	172.5	440	50,0	
		L	430,0	600,0	696,0	609,0	180	510	425,0	70,0	68,00	73,40	400,0	45,0	172.5	460	70,0	
XL		440,0	628,0	717,0	627,0	210	530	425,0	70,0	68,00	73,40	400,0	45,0	175	460	70,0		
XS		385	526	625	536	110	435	425,0	70	68.6	74	390	55	165	400,0	50,0		
S		415	550	664	573	130	460	425,0	75	68.6	74	390	55	170	420	50,0		
HI		M	425	568	680	589	150	485	425,0	75	68.6	74	390	55	172.5	440	50,0	
		L	435	596	700	607	180	510	425,0	75	68.6	74	390	55	172.5	460	70,0	
XL		445	624	721	625	210	530	425,0	75	68.6	74	390	55	175	460	70,0		